## Product data sheet Characteristics

# LA36300 3P 300A 600V LA MOULDED CASE CIRCUIT **BREAKER**

Product availability: Stock - Normally stocked in distribution facility





Price\*: 4944.00 USD



#### Main

Product or component type	Circuit breaker	
Range of product	I-Line	
Trip unit technology	Thermal-magnetic	
Breaking capacity code	LA	

#### Complementary

		mentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications
Main		ts for spe
Product or component type	Circuit breaker	
Range of product	I-Line	d 
Trip unit technology	Thermal-magnetic	, of th
Breaking capacity code	LA	reliabiliti
Complementary		ability or
Line Rated Current	300 A	g suit
Poles description	3P	Tinin
Breaking capacity	25 kA at 600 V AC 42 kA at 240 V AC 30 kA at 480 V AC	sed for deter
System Voltage	250 V DC 600 V AC	if to be us
AWG gauge	AWG 1600 kcmil (aluminium/copper) AWG 1250 kcmil (aluminium/copper)	and is no
Terminal identifier	AL400LA	itute for
Environment		s a subst
Product certifications	CSA UL listed	itended a
Ordering and shipping details		tion is not ir
Category	01040 - LA/LH BRKR, SW, MAG-GARD	nenta

#### Environment

Product certifications	CSA
	UL listed

### Ordering and shipping details

Category	01040 - LA/LH BRKR, SW, MAG-GARD	mente
Discount Schedule	DE2	
GTIN	00785901426240	H Pis c
Nbr. of units in pkg.	1	
Package weight(Lbs)	17.9699999999999	isc isc

Returnability	Υ	
Country of origin	MX	
Offer Sustainability		
Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1304 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

18 months

Contractual warranty

Warranty period